

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Trade name: OSCCAR Putty PLAST

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: professional use.

Application of the substance / the mixture Knife filler/ Surfacers

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Luxon Trade LTD,
14 Chase grove
Birmingham, B24 0HU
United Kingdom
Tel: +44 1213 680433
Fax: +44 1213 680642
info@osccar-paint.com

Further information obtainable from: info@osccar-paint.com

1.4 Emergency telephone number: 44 1213 680 433

* **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20-48/20: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R10: Flammable.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— EN —

Printing date 18.05.2015

V- 1

Revision: 18.05.2015

Trade name: OSCCAR Putty PLAST

(Contd. of page 1)

Hazard pictograms


GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P314 Get medical advice/attention if you feel unwell.
















P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Chemical characterisation: Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene  Xn R20-48/20-63;  Xi R36/38 R10  Flam. Liq. 3, H226;  Repr. 2, H361d; STOT RE 1, H372;  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-25%
	Polyamine amide salt (72243/00/2008.0038, Germany)  Xi R38;  N R51/53  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315	0.1-1%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy  Xn R65;  N R51/53 R66-67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H336	0.1-1%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures
General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Trade name: OSCCAR Putty PLAST

(Contd. of page 2)

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Trade name: OSCCAR Putty PLAST

(Contd. of page 3)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.
Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

*** SECTION 8: Exposure controls/personal protection**

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL (Great Britain)	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm
---------------------	--

DNELs

100-42-5 styrene

Dermal	DNEL	406 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	289 mg/m ³ (acute - systemic effects, workers) 306 mg/m ³ (acute - local effects, workers) 85 mg/m ³ (long-term - systemic effects, workers)

PNECs

100-42-5 styrene

PNEC	0.028 mg/l (freshwater environment) 0.0028 mg/l (marine environment) 0.04 mg/l (intermittent releases) 0.614 mg/kg (freshwater sediment environment) 0.0614 mg/kg (marine sediment environment) 0.2 mg/kg (soil) 5 mg/l (sewage treatment plants)
------	---

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep ignition sources away - Do not smoke.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

Printing date 18.05.2015

V- 1

Revision: 18.05.2015

Trade name: OSCCAR Putty PLAST

(Contd. of page 4)

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Pasty
Colour:	Dark grey
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.**Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C Undetermined.

Flash point: 31 °C**Flammability (solid, gaseous):** Not applicable.**Decomposition temperature:** Not determined.**Auto-ignition temperature:** Not determined.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

— EN —

Printing date 18.05.2015

V- 1

Revision: 18.05.2015

Trade name: OSCCAR Putty PLAST

(Contd. of page 5)

Explosion limits:	
Lower:	1.1 Vol %
Upper:	6.1 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	1.9 g/cm ³
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

* **SECTION 10: Stability and reactivity**

10.1 Reactivity No decomposition if used according to specifications.

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with peroxides and other radical forming substances.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Formation of toxic gases is possible during heating or in case of fire.

* **SECTION 11: Toxicological information**

11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

100-42-5 styrene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 7)

Printing date 18.05.2015

V- 1

Revision: 18.05.2015

Trade name: OSCCAR Putty PLAST

(Contd. of page 6)

Aspiration hazard Based on available data, the classification criteria are not met.

* **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:

100-42-5 styrene

EC50/48 h	4.7 mg/l (Daphnia magna)
EC50/72 h	4.9 mg/l (Pseudokirchnerella subcapitata)
LC50/96 h	4.02 mg/l (Pimephales promelas)

12.2 Persistence and degradability

100-42-5 styrene

Biodegradation	70.9 % (readily biodegradable)
----------------	--------------------------------

12.3 Bioaccumulative potential

100-42-5 styrene

BCF	13.5 (-)
log Pow	2.96 (-)

12.4 Mobility in soil

100-42-5 styrene

Koc	352 (-)
-----	---------

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* **SECTION 14: Transport information**

14.1 UN-Number

ADR, IMDG, IATA UN1866

14.2 UN proper shipping name

ADR 1866 RESIN SOLUTION
IMDG, IATA RESIN SOLUTION

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31


Printing date 18.05.2015

V- 1

Revision: 18.05.2015

Trade name: OSCCAR Putty PLAST

(Contd. of page 7)

14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
	
Class	3
Label	3
14.4 Packing group	
ADR, IMDG, IATA	
III	
14.5 Environmental hazards:	
Marine pollutant (IMDG):	
No	
14.6 Special precautions for user	
Danger code (Kemler):	
Warning: Flammable liquids.	
EMS Number:	
30	
F-E,S-E	
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Not applicable.	
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
Remarks:	ADR 2.2.3.1.5
IMDG	
Limited quantities (LQ)	5L
Remarks:	IMDG 2.3.2.5
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 9)

Trade name: OSCCAR Putty PLAST

(Contd. of page 8)

- H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H372 Causes damage to the hearing organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
R10 Flammable.
R20 Harmful by inhalation.
R36/38 Irritating to eyes and skin.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Repr. 2: Reproductive toxicity. Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Sources European Chemicals Agency, <http://echa.europa.eu/>

*** Data compared to the previous version altered.**